



REVISION RECORD

REV.	CONTENT	MOD.	DATE
△1	增加脱模斜度	XLM	2012/02/10
△2	第一次增加无效果, 再次增加脱模斜度	XLM	2012/02/22
△3	增加螺丝和螺母的有效牙长度	LDD	2013/07/29
△4	防止螺丝在使用中倾斜	LDD	2013/11/08
△5	改善盖板和本体的匹配	LDD	2014/12/10

NOTES:

1. Voltage Rating: 300V, Current Rating: 15A
2. PITCH: 5.08mm
3. Insulation Withstands Voltage: AC2500V/min
4. Insulation Resistance: 5MΩ or more at DC500V
5. Using Temperature Range: -40° C ~ +105° C
6. Suitable Electric Wire: 30-12AWG
7. Screw Torque Value: 0.4N.m

技术要求:

1. 额定电压: 300V, 额定电流: 15A
2. 间距: 5.08mm
3. 耐受电压值: AC 2500V/min
4. 绝缘电阻≥5兆欧
5. 使用条件: -40° ~ +105°
6. 适用线规: 30-12AWG
7. 螺丝扭力: 0.4N.m

	pitch dimension			Nominal dimension					— /
	over 0 to 6	over 6 to 10	over 10 to 24	over 0 to 30	over 30 to 60	over 60 to 100	over 100 to 150		
variable range	0 to 6	6 to 10	10 to 24	0 to 30	30 to 60	60 to 100	100 to 150	□ ○	
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0 0.05/10	

7	LC1-耳朵螺丝	SPOYA255101V	2	碳钢	三价铬钝化彩锌
6	LC3-5.08-夹子	1009B0002AV	P	磷青铜	镀镍
5	LC3-5.08-方盒	F1A0ALC358AV	P	碳钢	三价铬钝化彩锌
4	LC3-5.08-压块	1009B0001AV	P	碳钢	三价铬钝化彩锌
3	LC3-5.08-螺丝	SPOYA256501V	P	碳钢	三价铬钝化彩锌
2	LC3-5.08-盖子	1009C0YXXAV	1	PA66-V0	
1	LC3M-5.08-本体	1009M0YXXAV	1	PA66-V0	

NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	ARKINE	DATE	2011/02/24	UNITS	mm
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				DWG NO.	SP-2-1009002
					REV: V5

上海联捷电气有限公司  
Shanghai Blinker Electric Co., Ltd

TITLE

LC3M-5.08-XXP-1Y-00A  
LC3M-5.08-成品