



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
①	初版发行		

**NOTES1:**

**UL Standard:**

1.Voltage Rating: 300V, Current Rating: 8A

2.Suitable Electric Wire: 28-16AWG

**IEC Standard:**

1.Voltage Rating: 160V, Current Rating: 8A

2.Suitable Electric Wire: 26-14AWG

**NOTES2:**

1.Pitch: 3.81mm

2.Withstand Voltage : AC2500V for 1 minute

3.Insulation Resistance : 500MΩ / DC500V

4.Using Temperature Range : - 40℃ ~ + 105℃

**技术要求1:**

**UL 标准:**

1. 额定电压: 300V, 额定电流: 8A

2. 适用线规: 28~16AWG

**IEC 标准:**

1. 额定电压: 160V, 额定电流: 8A

2. 适用线规: 26~14AWG

**技术要求2:**

1. 间距: 3.81mm

2. 耐电压值: AC2500V/min

3. 绝缘阻抗: 500MΩ/DC500V

4. 使用条件: -40℃~+105℃

	pitch dimension			Nominal dimension					— □ ○
	over 0 to 6	over 6 to 10	over 10 to 24	over 0 to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	
variable range	0 to 6	6 to 10	10 to 24	0 to 30	30 to 60	60 to 100	100 to 150	150	0.05/10
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

6	LZ1-5.08-螺母	SM00B250000V	2	黄铜	
5	LC60-3.81五金件	2079B0001AV	P	磷青铜	镀亮锡
4	LC6-3.81-弹片	F2A0DLC638BV	P	不锈钢	
3	LC6-3.81-按钮	1043D0YXXAV	P	POM	
2	LC60MG-3.81-盖板	2081N0YXXAV	1	PA66-V0	
1	LC60N-3.81-本体	2082A0YXXAV	1	PA66-V0	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	WY	DATE	2022/10/21	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				DWG NO.	SP-1-2082140
				REV:	V0
 <b>上海联捷电气有限公司</b> Shanghai Elinker Electric Co., LTD				TITLE	LC60NMG-3.81-XXP-1Y-00A
					LC60NMG-3.81-成品