



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
①	初版发行		

NOTES1:

UL Standard:

- 1.Voltage Rating: 300V, Current Rating: 8A
- 2.Suitable Electric Wire: 28-16AWG

IEC Standard:

- 1.Voltage Rating: 160V, Current Rating: 8A
- 2.Suitable Electric Wire: 26-14AWG

NOTES2:

- 1.Pitch : 3.81mm
- 2.Withstand Voltage : AC2500V for 1 minute
- 3.Insulation Resistance : 500MΩ / DC500V
- 4.Using Temperature Range : - 40℃ ~ + 105℃

技术要求1:

UL 标准:

1. 额定电压: 300V, 额定电流: 8A
2. 适用线规: 28~16AWG

IEC 标准:

1. 额定电压: 160V, 额定电流: 8A
2. 适用线规: 26~14AWG

技术要求2:

1. 间距: 3.81mm
2. 耐电压值: AC2500V/min
3. 绝缘阻抗: 500MΩ/DC500V
4. 使用条件: -40℃~+105℃

6	LZ1-5.08-螺母	SM00B25000V	2	黄铜		
5	LC60-3.81五金件	2079B0001AV	P	磷青铜	镀亮锡	
4	LC6-3.81-弹片	F2A0DLC638BV	P	不锈钢		
3	LC6-3.81-按钮	1043D0YXXAV	P	POM		
2	LC60MG-3.81-盖板	2081N0YXXAV	1	PA66-V0		
1	LC6-3.81-本体	1043A0YXXAV	1	PA66-V0		
NO.	NAME OF PART		NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	WY	DATE	2020/06/01	UNITS	MM	THIRD ANGLE PROJECTION SHEET
CHK.		DATE		SIZE	A4	1 of 1
APP.		DATE		SCALE	1:1	DWG NO. SP-1-2081140 REV: V0
上海联捷电气有限公司 Shanghai Elinker Electric Co., LTD					TITLE	LC60MG-3.81-XXP-1Y-00A
						LC60MG-3.81-成品

	pitch dimension			Nominal dimension					— —
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	0 to 6	6 to 10	10 to 24	0 to 30	30 to 60	60 to 100	100 to 150	150 to	
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10