

REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

**NOTES1:**

UL Standard:

1.Voltage Rating: 300V, Current Rating: 10A

**NOTES2:**

1.Pitch : 5.08mm

2.Withstand Voltage : AC2500V for 1 minute

3.Using Temperature Range : - 40℃ ~ + 105℃

4.Suitable Electric Wire: 26-12AWG

技术要求1:

UL 标准:

1. 额定电压: 300V, 额定电流: 10A


技术要求2:

1. 间距: 5.08mm

2. 耐电压值: AC2500V/min

3. 使用条件: -40℃~+105℃

4. 适用线规: 26~12AWG



5	LC60-5.08五金件	2083B0001AV	P	磷青铜	镀锡
4	LC6-5.08-弹片	F2A0DLC658BV	P	不锈钢	
3	LC6-5.08-按钮	1020D0Y01AV	P	POM	
2	LC60-5.08-盖板	2083C0YXXAV	1	PA66-V0	
1	LC60N-5.08-本体	2084A0YXXAV	1	PA66-V0	
NO.	NAME OF PART	NO. OF PART	Q' TY	MATERIAL	NOTES
DES.	CMZ	DATE	2025/03/26	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				DWG NO.	SP-2-208401
				REV:	V0
 <b>上海联捷电气有限公司</b> Shanghai Elinker Electric Co., Ltd				TITLE	LC60N-5.08-XXP-1Y-00A
					LC60N-5.08-成品

	pitch dimension			Nominal dimension					— /
	over 0 to 6	over 6 to 10	over 10 to 24	over 0 to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	
variable range	0	6	10	0	30	60	100	150	□ ○
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10